

BLANK PAGE



IS: 3555 - 1983 (Reaffirmed 1994)

Indian Standard

SPECIFICATION FOR COTTON SINGLETS, WHITE WITH BLUE WELTING

(First Revision)

First Reprint JANUARY 2001

UDC 677 21 355.14

Copyright 1983

BUREAU OF INDIAN STANDARDS MANAK BHAVAN. 9 BAHADUR SHAH ZAFAR MARG NEW DEI HI 110002

AMENDMENT NO. 1 SEPTEMBER 1998 TO

IS 3555: 1983 SPECIFICATION FOR COTTON SINGLETS, WHITE WITH BLUE WELTING

(First Revision)

(Page 5, clause 4.2) — Delete the word 'Scouring Loss' appearing in the clause and substitute 'IS 9469: 1991" for 'IS: 9469 - 1980".

(Page 5, foot-note with '*' mark) — Substitute the existing with the following:

"Textiles - Fabric, cotton, plain knitted - Specification (first revision)."

(Page 6, Table 2, col 10) — Delete the requirement of Mass of 10 Singlets.

(Page 8, clause 7.4) — Under 'Characteristic(s)' delete the words 'scouring loss'.

(Page 9, clause A-3) - Delete.

(TX 10)

Indian Standard

SPECIFICATION FOR COTTON SINGLETS, WHITE WITH BLUE WELTING

(First Revision)

Hosiery Sectional Committee, TDC 15

α	• •	
,	airn	

SHRI R. R. PRASAD

Members

Shri K. L. Ahuja SHBI A. T. BABAK

SHRI B. D. DUBE (Alternate)

WG COR V. B. BATRA SHRI D. K. SRIVABTAVA (Alternate)

SHBI G. N. CHATTERJEE

SHRIS. N. HALDAR (Alternate)

SHRI D. GHOSE

SHRI D. PAUL (Alternate)

SHRI M. S. GILL

SHRIJ, S. GREWAL (Alternate)

SHRI R. C. JAIN

SHRI S. P. KAPUR

SHRI G. KARTHIKEYAN

SHRI ARVIND K. KIKANI

SHRI MELA RAM

SHRIK, K. GUPTA (Alternate)

SHRI R. NATARAJAN

SHRI S. T. NOTANI

Federation of Hosiery Manufacturers' Association of India, Bombay

Representing

Scale Industries, New Delhi

(Inspection Wing), New Delhi

Knit Fab Industries, Chandigarh

Ministry of Defence (DGI)

Ministry of Defence (R&D)

Calcutta

Chandigarh

tion, Tirupur

Office of the Development Commissioner, Small

Directorate General of Supplies & Disposals

The Bengal Hosiery Manufacturers' Association,

Directorate of Industries, Government of Punjab,

Delhi Hosiery Udyog Mandal (Regd), Delhi

The Hosiery Industry Federation, Ludhiana The South India Hosiery Manufacturers' Associa-

Southern India Mills' Association, Coimbatore The Northern India Hosiery Manufacturers'

SHRI RATNAKAR ASGEKAR (Alternate)

SHRIJ. L. OSWAL

Rank Knitting Mills, Tirupur

Corporation, Ludhiana

Wool & Woollens Export Promotion Council. Bombay

(Continued on page 2)

© Copyright 1983

BUREAU OF INDIAN STANDARDS

This publication is protected under the Indian Copyright Act (XIV of 1957) and reproduction in whole or in part by any means except with written permission of the publisher shall be deemed to be an infringement of copyright under the said Act.

18: 3555 - 1983

(Continued from page 1)

Members

PRINCIPAL, GOVERNMENT INSTI-TUTE OF TEXTILE CHEMISTRY AND KNITTING TECHNOLOGY, LUDHIANA

SHRI A. S. RAMA RAO

OFFICER, INSPECTING REGIONAL OFFICE OF TEXTILES COMMITTEE, COIMBATORE (Alternate I) OFFICER, INSPECTING REGIONAL OFFICE OF TEXTILES COMMITTEE,

LUDHIANA (Alternate II)

Shri A. I S. Rao Off Shri V. K. Srivastava (Alternate) Shri B. I. Sharma We

DR V. R. SIVAKUMAR

SHRT B. K. THAPAR

SHRIJ. N. VOHBA

Representing

Directorate of Industries and Industrial Training, Government of Punjab, Chandigarh

Textiles Committee, Bombay

Office of the Textile Commissioner, Bombay

West Bengal Hosiery Association, Calcutta

The South India Textile Research Association, Coimbatore

B. K. Thapar Hosiery Works. Ludhiana

Punjab State Hosiery and Knitwear Development Corporation Ltd, Chandigarh

SHRI P. K. BHARDWAJ (Alternate)

SHRI S. M. CHARRABORTY, Director (Tex)

Director General, ISI (Ex-officio Member)

Secretary

SHRI R. K. DUA Deputy Director (Tex), ISI

Indian Standard

SPECIFICATION FOR COTTON SINGLETS, WHITE WITH BLUE WELTING

(First Revision)

0. FOREWORD

- 0.1 This Indian Standard (First Revision) was adopted by the Indian Standards Institution on 8 March 1983, after the draft finalized by the Hosiery Sectional Committee had been approved by the Textile Division Council.
- 0.2 This standard has been revised to make it up to date by specifying the conformity of plain knitted fabric, used in the manufacture of singlets to IS: 9469-1980* besides effecting other necessary modifications.
- 0.3 The standards of Weights and Measures Act, 1976 stipulate the use of International System of Units in the country. In order to familiarize the industry with this system the recommended SI units for use in the textile industry are given in Appendix B.
- 0.4 For the purpose of deciding whether a particular requirement of this standard is complied with, the final value, observed or calculated, expressing the result of a test or analysis, shall be rounded off in accordance with IS: 2-1960†. The number of significant places retained in the rounded off value should be the same as that of the specified value in this standard.

1. SCOPE

- 1.1 This standard prescribes constructional details and other requirements of cotton singlets, white with blue welting around the neck and armholes.
- 1.2 This standard does not specify general appearance, feel, lustre, degree of whiteness and shade of welting of the singlets (see also 4.3).

^{*}Specification for plain-knitted cotton fabric,

[†]Rules for rounding off numerical values (revised).

1**S** : 3555 - 1983

2. TERMINOLOGY

2.1 For the purpose of this standard, the definitions given in IS: 3596-1967* shall apply.

3. MANUFACTURE

- 3.1 Fabric The singlets shall be tailored out of well and evenly knitted tubular fabric conforming to IS: 9469-1980†. The welting round the neck and armholes shall be of the same material as that of the body and of navy blue colour of the shade as agreed to between the buyer and the seller.
- 3.1.1 The width of the fabric roll from which the singlets are to be tailored shall correspond to the size of the singlets.
- 3.2 Shape The shape of the singlets shall generally be as shown in Fig. 1.




Fig. 1 Singlet

3.3 Seams and Stitches — The type of stitch and count of sewing thread for stitching various portions of singlets shall be as given in Table 1.

[•]Glossary of terms relating to hosiery.

[†]Specification for plain-knitted cotton fabric.

TABLE 1 SEAMS AND STITCHES

(Clause 3.3)

	(Gran	36 3.3)	
Portion to be Stitched	TYPE OF STITCH	Thread* in the Needle	THREAD® IN THE LOOPER(8)
(1)	(2)	(3)	(4)
Hemming at the bottom	2-thread overlock	One strand of 9'8 tex × 3 (cotton count 60s/3)	$ ext{tex} imes 2$ (cotton
Shoulder pieces, neck and arm- holes	3-thread overlock	One strand of 9.8 $tex \times 3$ (cotton count $60s/3$)	Two strands of 15 tex × 2 (cotton count 40s/2)

^{*}Cotton sewing threads shall conform to IS: 1720-1978 'Specification for cotton sewing threads (second revision).

3.4 Freedom from Defects — The singlets shall be reasonably free from manufacturing defects, such as mends, ladders, dropped stitches, holes, cuts, missed stitches and defective stitching and hemming. The singlet shall also be free from chemical damages like defective bleaching welting shall be free from streaks, stains and uneven dying. The stitching shall be such that the face of the fabric at the seam does not show any wrinkles.

4. REQUIREMENTS

4.1 Dimensions and Mass — The dimensions and mass of the singlets of a particular size shall conform to the requirements of Table 2 read with Fig. 1.

Note — Size of the singlets is denoted by a number which is the numerical value of chest girth in centimetres.

- 4.2 Other Requirements The singlets shall satisfy the requirements in respect of dimensional change due to relaxation, scouring loss, pH value of aqueous extract and colour fastness as given in IS: 9469-1980*.
- 4.3 Sealed Sample If in order to illustrate or specify the undeterminable characteristics, such as general appearance, degree of whiteness and shade of welting, a sample has been agreed upon and sealed, the supply shall be in conformity with the sample in such respects.
- 4.3.1 The custody of the sealed sample shall be a matter of prior agreement between the buyer and the seller.

^{*}Specification for plain-knitted cotton fabric.

		TABLE 2		DIMENSIONS AND MASS OF SINGLETS	MASS OF S	INGLETS			
			Ŋ)	(Clause 4.1 and Fig. 1)	ig. 1)				
Size	Width	LENGTH	Wіртн	NECK OPENING	PENING	ARM	HEM AT BOTTOM	Width Of	Mass of 10
	Across Crest A	В	ACROSS SHOULDERS G	Width	Depth	LENGTH F		Welting H	Singlets Min
5	(2)	(3)	(4)	(5)	(9)	(7)	(8)	(6)	(10)
Ξ	E	C B C	C III	CB	СШ	СШ	cm	CIB	kg
Ċ	40.0	70.0	38.0	13.0	13.0	18.0	2.5	2.5	0.910
00 .	5 c.		4 0.0	13.5	13.5	0.61	2.5	2.5	1.050
ç ç	0.74	75.0	43.0	14 0	14.0	20.0	2.5	2.5	1.190
S 6	4.7.k	78.0	46.0	14-5	14.5	21.0	2.5	2.5	1-330
93 100	50.0	0.08	48.0	15.0	15.0	22.0	2.5	2.5	1.470
Tolerance	1:0	∓ 2.0	± 1.5	1.0	1:0	# 10	± 0.5	± 0.5	
Method of Test	A-2	A-2	A-2	A-2	A-2	A ±2	A-2	A-2	A-3

5. MARKING

- 5.1 A suitable cloth label shall be securely stitched to each singlet at the inside of the neck portion (backside) on which the following shall be indicated:
 - a) Size;
 - b) Manufacturer's name, initials or trade-mark, if any; and
 - c) Any other information required by the buyer.
 - 5.1.1 The product may also be marked with Standard mark.
- 5.1.1.1 The use of the Standard Mark is governed by the provisions of the Bureau of Indian Standards Act, 1986 and the Rules and Regulations made thereunder. The details of conditions under which the licence for the use of Standard Mark may be granted to manufacturers or producers may be obtained from the Bureau of Indian Standards.

6. PACKING

6.1 The singlets shall be packed in accordance with IS: 3086-1965* or IS: 3325-1965*, as the case may be.

7. SAMPLING

- 7.1 Lot In any consignment, all the singlets of the same size manufactured from the same quality of fabric shall constitute a lot.
- 7.2 The conformity of a lot to the specification shall be determined on the basis of the test carried out on the singlets selected from the lot.
- 7.3 Unless otherwise agreed to between the buyer and the seller, a number of singlets, depending on the lot size, shall be selected at random according to col 1 and 2 of Table 3.

^{*}Code for seaworthy packaging of cotton hosiery yarn and goods.

[†]Code for inland packaging of cotton hosicry yarn and goods.

TABLE 3 SAMPLE SIZE AND PERMISSIBLE NUMBER OF NON-CONFORMING SINGLETS

(Clauses 7.3)

No. of Singlets in the Lot	For Dimensions and	FOR DIMENSIONS AND VISUAL INSPECTION	
IN THE LOT	Number of Singlets to be Inspected	Permissible Number of Non-Conforming Pairs	SINGLETS TO BE TESTED FOR CHEMICAL CHARACTERISTICS
(1)	(2)	(3)	(4)
U p to 100	10	0	3
101 ,, 300	20	1	3
301 ,, 500	30	2	5
501 ,, 1 000	50	3	5
1 001 and above	80	5	8

7.4 The number of singlets to be inspected and criterion for conformity for each characteristic shall be as follows:

Characteristic(s)	No. of Singlets to be Inspected	Criterion for Conformity
Visual inspection and Dimensions	According to col 2 of Table 3	Non-conforming singlets shall not exceed the corresponding number given in col 3 of Table 3
Mass	Sets of 10 singlets obtained from those selected according to col 2 of Table 3	All the observations shall satisfy the relevant requirement
Dimensional change, scouring loss, pH value and colour fastness	According to col 4 of Table 3	All the test results shall satisfy the relevant requirement

APPENDIX A

(Table 2)

METHODS OF TEST

A-1. CONDITIONING OF TEST SPECIMENS AND ATMOS-PHERIC CONDITIONS FOR TESTING

A-1.1 The test specimens shall be conditioned and tested in the standard atmosphere as given in IS: 6359-1971*.

A-2. DIMENSIONS

A-2.1 Take a singlet from the test sample. Lay it flat on a horizontal surface. Remove all creases and wrinkles without distorting it. Measure, correct to the nearest 5 mm, the dimensions given in Table 1.

A-3. MASS

A-3.1 Take a set of 10 singlets from the test sample. Condition to moisture equilibrium for 24 hours (see A-1.1) and weigh to an accuracy of 10 g.

APPENDIX B

(Clause 0.3)

RECOMMENDED SI UNITS FOR TEXTILES

SL	CHARACTER-	SI Uni	T	APPLICATION	
No.	ISTIC	Unit	Abbrevia- tion		
(1)	(2)	(3)	(4)	(5)	
1.	Length	Millimetre Millimetre, centimetre	mm mm, cm	Fibres Samples, test specimens (as appropriate)	
		Metre	m	Yarns, ropes, cor- dage, fabrics	
2.	Width	Millimetre Centimetre Millimetre, centimetre Centimetre, metre	mm cm mm, cm	Narrow labrics Other fabrics Samples, test specimens (as appropriate) Carpets, druggets,	
		centimetre, mene	ciii, iii	DURRIES (as appropriate)	

^{*}Method for conditioning of textiles.

IS: 3555 - 1983

SL	CHARACTER-	SI Uni	т	Application
No.	18110	Unit	Abbrevia- tion	
(1)	(2)	(3)	(4)	(5)
3.	Thickness	Micrometre (micron) Millimetre	μm nim	Delicate fabrics Other fabrics, car- pets, felts
4.	Linear den- sity	Tex Millitex Decitex Kilotex	tex mtex dtex ktex	Yarns Fibres Filaments, filament yarns Slivers, ropes, cordage
5.	Diameter	Micrometre (micron) Millimetre	μm mm	Fibres Yarns, ropes, cor- dage
6.	Circumfer- ence	Millimetre	mm	Ropes, cordage
7.	Threads in fabric:			Woven fabrics (as appropriate)
	a) Length- wise	Number per centimetre Number per decimetre	ends/cm ends/dm	
	b) Width- wise	Number per centimetre Number per decimetre	picks/cm picks/dm	
8.	Warp threads in loom	Number per centimetre	ends/cm	Reeds
9.	Stitches in knitted fabric			Knitted fabrics (as appropriate)
	a) Length- wise	Courses per centimetre Courses per decimetre	courses/cm courses/dm	
	b) Width- wise	Wales per centimetre Wales per decimetre	wales/cm wales/dm	
10.	Stitch length	Milli netre	mm	Knitted fabrics, made-up fabrics
11.	Mass per unit	Grams per square metre	g/m²	Fabrics
12.	Mass per unit length	Grams per metre	g/m	Fabrics
13.	Twist	Turns per centimetre Turns per metre	turns/cm turns/m	Yarns, ropes, cordage (as appropriate)

IS: 3555 - 1983

SL	CHARACTER-	SI Unit		APPLICATION
No.	isti0	Unit	Abbrevia- tion	
(1)	(2)	(3)	(4)	(5)
14.	Test or gauge length	Millimetre, centimetre	mm, cm	Fibre, yarn and fab- ric specimens (as appropriate)
15.	Breaking load	Millinewton	mN	Fibre. delicate yarns (individual or skeins)
		Newton	N	Strong yarns (indi- vidual or skeins), ropes, cordage, fabrics
16.	Breaking len- gth	Kilometre	km	Yarns
17.	Tenacity	Millinewton per tex	mN/tex	Fibres, yarns (indi- vidual or skeins)
18.	Twist factor or twist mul- tiplier	Furns per centimetre x square root of tex Turns per metre x square root of tex	turns/cm ×√tex turns/m ×√tex	Yarns (as appro- priate)
19.	Bursting strength	Newton per square cen- timetre	N/cm^2	Fabrics
20.	Tear strength	Millinewton, newton	mN, N	Fabrics (as appropriate)
21.	Pile height	Millimetre	mm	Carpets
22.	Pile density	Mass of pile yarn in grams per square metre per millimetre pile height	g/m²/mm pile height	Pile carpets
23.	Elastic modu- lus	Millinewton per tex per unit deformation	mN/tex/unit deformation	Fibres, yarns, strands

BUREAU OF INDIAN STANDARDS

Headquarters:

Manak Bhavan, 9 Bahadur Shah Zafar Marg, NEW DELHI 110002 Telephones 323 0131, 323 3375, 323 9402 Fax 91 11 3234062, 91 11 3239399, 91 11 3239382

	Telegrams Ma (Common to	anaksanstha all Offices)
Central Laboratory:		Telephone
Plot No 20/9, Site IV, Sahibabad Industrial Area, SAHIBABAD 2	201010	8-77 00 32
Regional Offices:		
Central Manak Bhavan, 9 Bahadur Shah Zafar Marg, NEW DE	LHI 110002	323 76 17
*Eastern 1/14 CIT Scheme VII M, VI P Road, Maniktola, CALC	CUTTA 700054	337 86 62
Northern SCO 335-336, Sector 34-A, CHANDIGARH 160022		60 38 43
Southern CIT Campus, IV Cross Road, CHENNAI 600113		235 23 15
†Western Manakalaya, E9 Behind Marol Telephone Exchange, a MUMBAI 400093	Andheri (East),	832 92 95
Branch Offices:		
'Pushpak', Nurmohamed Shaikh Marq, Khanpur, AHMEDABAD 3	80001	550 13 48
‡Pecnya Industrial Area, 1st Stage, Bangalore - Tumkur Road, BANGALORE 560058		839 49 55
Gangotri Complex 5th Floor, Bhadbhada Road, T.T. Nagar, BHC	PAL 462003	55 40 21
Plot No 62-63, Unit VI, Ganga Nagar, BHUBANESHWAR 75100	01	40 36 27
Kalaikathir Buildings, 670 Avinashi Road, COIMBATORE 641037		21 01 41
Plot No 43, Sector 16 A, Mathura Road, FARIDABAD 1210.71		8-28 88 01
Savitri Complex, 116 G T Road, GHAZIABAD 201001		8-71 19 96
53/5 Ward No 29, R G Barue Road, 5th By-lane, GUWAHATI	781003	54 11 37
5-8-58C, L. N. Gupta Marg, Nampally Station Road, HYDERABA	AD 500001	20 10 83
E-52, Chitaranjan Marg, C-Scheme, JAIPUR 302001		37 29 25
117/418 B, Sarvodaya Nagar, KANPUR 208005		21 68 76
Seth Bhawan, 2nd Floor, Behind Leela Cinema, Naval Kishore R LUCKNOW 226001	oai',	23 89 23
Patliputra Industrial Estate, PATNA 800013		26 23 05
T C No 14/1421, University P O Palayam, THIRUVANANTHAPURAM 695034		6 21 17
NIT Building, Second Floor, Gokulpat Market, NAGPUR 440010		52 51 71
Institution of Engineers (India) Building, 1332 Shivaji Nagar, PU	JNE 411005	32 36 35
*Sales Office is at 5 Chowringhee Approach, P O Princep Street CALCUTTA 700072	et,	27 10 85
†Sales Office is at Novelty Chambers, Grant Road, MUMBAI 40)0007	309 65 28
‡Sales Office is at F' Block, Unity Building, Narashimaraja Squa		222 39 71
BANGALORE 560002	,	